



Monitor Cameras



	Reconyx HC500	Reconyx HC550	Reconyx HC600	ReconyxSC950	Reconyx SM750	Moultrie M990i	Moultrie M1100i	Moultrie P150	
Flash Type/Visibility	Infrared / Low Glow	White Flash	Infrared / Zero Glow	Infrared / Zero Glow	Infrared / Zero Glow	Zero Glow	Zero Glow	Infrared/Zero Glow	
Image sensor	3.2 MP	3.2 MP	3.2 MP	3.2 MP	1.3 MP	10 MP	12 MP	8 MP	
Maximum SD card	32 GB	32 GB	32 GB	32 GB	32 GB	32 GB	32 GB	32 GB	
Flash range	15 m	10 m	18 m	15 m	15 m	18 m	20 m	25 m	
PIR Range	25 m	25 m	15 m	15 m	15 m	15 m	15 m	15 m	
Delay between multiple shots	0.5,1,3,5,10 sec	0.5,1,3,5,10 sec	0.5,1,3,5,10 sec	0.5,1,3,5,10 sec	0.5,1,3,5,10 sec	1 sec	1 sec		
Video resolution	N/A	N/A	N/A	N/A	N/A	VGA: 848 x 440 HD: 1280 x 720	HD: 1280 x 720 Full HD: 1920 x 1080	VGA: 848 x 480 HD: 1280 x 720	
Maximum video length	N/A	N/A	N/A	N/A	N/A	90 sec	90 sec	90 sec day 30 sec night	
Sound Recording	N/A	N/A	N/A	N/A	N/A	Yes	N/A	N/A	
Number of photos per trigger	1,2,3,5,10	1,2,3,5,10	1,2,3,5,10	1,2,3,5,10	1,2,3,5,10	1-3	1-3	1-3	
Delay between triggers	0,15,30 sec, 1,3,5 min	0,15,30 sec, 1,3,5 min	0,15,30 sec, 1,3,5 min	0,15,30 sec, 1,3,5 min	0,15,30 sec, 1,3,5 min	5,15,30 sec, 1,5,10,30 min	5,15,30 sec, 1,5,10,30 min	5,15,30 sec, 1,5,10,30,60 min	
Time lapse	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
Motion sensor scheduling	N/A	N/A	N/A	Hours of day and days per week	Hours of day and days per week	Hybrid mode: time-lapse during day and motion sensing at night	Hybrid mode: time-lapse during day and motion sensing at night	Hybrid mode: time-lapse during day and motion sensing at night	
Loop recording	N/A	N/A	N/A	Yes	Yes	Yes	Yes	Yes	
Trigger speed	0.2 sec	0.2 sec	0.2 sec	0.2 sec	0.1 sec	< 1 sec	0.5 sec	< 1 sec	
Viewing screen size	N/A	N/A	N/A	N/A	N/A	50 mm internal	50 mm internal	N/A	
Size (H x D x W)	140 x 83 x 116 mm	140 x 83 x 116 mm	140 x 83 x 116 mm	140 x 83 x 116 mm	140 x 83 x 116 mm	127 x 100 x 75 mm	127 x 100 x 75 mm	165 x 115 x 115 mm	
Ext power socket	No	No	No	Special Order	Special Order	Yes	Yes	Yes	
Batteries	12 x AA Lithium - Yes Ni-Mh - Yes Alkaline - Yes	12 x AA Lithium - Yes Ni-Mh - Yes Alkaline - No	12 x AA Lithium - Yes Ni-Mh - Yes Alkaline - No	12 x AA Lithium - Yes Ni-Mh - Yes Alkaline - No	12 x AA Lithium - Yes Ni-Mh - Yes Alkaline - No	12 x AA Lithium - Yes Ni-Mh - Yes Alkaline - No	8 x AA	4 x D	6 x C
Picture stamp	Date, Time, Temp, Moon Phase	Date, Time, Temp, Moon Phase	Date, Time, Temp, Moon Phase	Date, Time, Temp, Moon Phase	Date, Time, Temp, Moon Phase	Date, Time, Temp, Moon Phase, Custom name	Date, Time, Temp, Moon Phase, Custom name	Date, Time, Temp, Moon Phase, Custom name	
Operating temp range	-30 to 50 deg C	-30 to 50 deg C	-30 to 50 deg C	-30 to 50 deg C	-30 to 50 deg C				
Password protection	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
Python lock usable	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	

Monitor Cameras



	Moultrie P150i	ScoutGuard EcoGlow	ScoutGuard SG560P-8M	ScoutGuard Zero Glow 8M	ScoutGuard Zero Glow 10M	SpyPoint Tiny W3	SpyPoint BF12
Flash Type/Visibility	Zero Glow	White Flash	Infrared / Zero Glow	Zero Glow	Zero Glow	Infrared / Zero Glow	Infrared / Zero Glow
Image sensor	8 MP	8 MP	8 MP	8 MP	10 MP	10 MP	12 MP
Maximum SD card	32 GB	32 GB	32 GB	32 GB	32 GB	32 GB	32 GB
Flash range	20 m	15 m	Adjustable 14/22 m	Adjustable 8/15 m	Adjustable 8/15 m	Auto adjusts up to 15 m	15 m
PIR Range	15 m	15 m	25 m	25 m	25 m	1.5 - 15 m	Adjustable from 1.2-18 m
Delay between multiple shots		1 sec	2 sec	2 sec	2 sec	10 sec,1,3,5,10,15,30 min	3 sec
Video resolution	VGA: 848 x 480 HD: 1280 x 720	640 x 480	640 x 480	1280 x 720	1280 x 720	1280 x 720	1280 x 720
Maximum video length	90 sec day 30 sec night	1-10 sec	1-60 sec	1-60 sec	1-60 sec	10-90 sec	10-90 sec
Sound Recording	N/A	N/A	N/A	N/A	N/A	Yes	Yes
Number of photos per trigger	1-3	1-10	1-3	1-3	1-3	1-6 stand-alone 1-2 wireless linked	1-6
Delay between triggers	5,15,30 sec, 1,5,10,30,60 min	0-60 sec	0,5,10,15 sec to 60 min	0,5,10,15 sec to 60 min	0,5,10,15 sec to 60 min	10 sec - 30 min	10 sec - 30 min
Time lapse	Yes	Yes	Yes	Yes	Yes + motion sensing at same time	Yes	Yes
Motion sensor scheduling	Hybrid mode: time-lapse during day and motion sensing at night	Yes	Yes	Yes	Yes	Yes	Yes
Loop recording	Yes					Yes	
Trigger speed	< 1 sec	1.2 sec	1.2 sec	1.2 sec	1.2 sec	1.5 sec	0.85 sec
Viewing screen size	N/A	48 mm internal	48 mm internal	48 mm internal	48 mm internal	60 mm internal	76 mm internal
Size (H x D x W)	165 x 115 x 115 mm	138 x 67 x 102 mm	138 x 67 x 102 mm	138 x 67 x 102 mm	138 x 67 x 102 mm	8.8 x 6.8 x 12	175 x 67 x 130 mm
Ext power socket	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Batteries	6 x C	8 x AA Lithium - Yes Ni-Mh - Yes Alkaline - Yes	8 x AA Lithium - Yes Ni-Mh - Yes Alkaline - Yes	8 x AA Lithium - Yes Ni-Mh - Yes Alkaline - Yes	8 x AA Lithium - Yes Ni-Mh - Yes Alkaline - Yes	6 x AA Lithium - Yes Ni-Mh - No Alkaline - Yes	6 x AA Lithium - Yes Ni-Mh - No Alkaline - Yes
Picture stamp	Date, Time, Temp, Moon Phase, Custom name	Date, Time	Date, Time	Date, Time	Date, Time	Date, Time, Temp, Moon Phase	Date, Time, Temp, Moon Phase
Operating temp range						-20 - + 50 deg C	-20 - + 50 deg C
Password protection	Yes	No	No	No	No	No	No
Python lock usable	Yes	No	No	No	No	Yes	Yes